

Drainsafe™...Your Circle Of Safety

ASME/ANSI A112.19.8 2007 Standard and VGB 2008 Compliant

Drainsafe™ DS 360 & DS 360M

- DS 360M will retrofit 5" - 8" dia. sumps
- Universal fastener kit and security tool included with both models
- Either model works on dual drain as well as single suction outlets
- Certified Safe flow of 123 G.P.M.
- Able to be installed on a Vertical or Horizontal plane
- Both DS 360 & DS 360M are pool cleaner friendly
- 27 sq. in. open surface area minimizes potential "Differential Hold Down Forces" of dual drain systems



DS 360

DS 360 M

Drainsafe™ DS 360 X (9x9 Kit)

- Includes orange head safety screws for regulatory official visual inspections
- Minimizes potential "Differential Hold Down Forces" of dual drain systems
- Certified safe flow rate of 160 G.P.M. (@1.9 f.p.s.)
- Works on dual drain as well as single suction outlets
- **SOLD AS A COMPLETE KIT ONLY!!**
- **FLOOR MOUNT ONLY!!**



DS 360 X

DS Adapter Shims
(for deeper frames)

DS 9x9 Adapter Plate

Certified IAPMO R&T (International Association of Plumbing and Mechanical Officials)

DS Mud Ring (or optional DS Adapter Ring)

- Constructed of Rigid PVC Material & Chamfered (beveled) for smooth Hydraulic Flow (for use with DS 360 or DS 360M Covers Only)
- Optional Adapter Ring attaches to existing sumps with 7 5/8" bolt pattern using provided 316 grade stainless steel screws



Adapter Ring
(Optional)

DS Mud Ring
(or optional Adapter Ring)

Check Your Local Distributor for Pricing and Availability
for additional safety information go to www.drainsafe.com

NEVER LEAVE A CHILD ALONE BY WATER... ANY WATER!